

EDFA Optribution Amplifier Modules



The final product may vary from the above image depending on the options selected.

Products

DEV 7415 EDFA Optribution Pre-Amplifier Module;
1529...1565 nm; SC/APC

DEV 7425 EDFA Optribution Boost-Amplifier Module;
1529...1565 nm; SC/APC

Features

- EDFA Amplifier Modules for the Integration in a DEV 7113 Chassis
- High Gain and low Noise Figure EDFA Amplifiers
- Automatic Output Power Control (APC) Operation Mode
- Monitoring of Input and Output Optical Power Level
- Front Panel Status and Alarm LEDs

Technical Data DEV 7415 & DEV 7425

	Value	Condition
Common Optical Specifications		
Number of Optical Inputs	1	
Number of Optical Outputs	1	
Optical Connector	SC/APC, E2000/HRL, or FC/APC	Standard is SC/APC
Laser Class (according to IEC 60 825-1)	Class 1M (low Risk to Eyes, no Risk to Skin)	
Fiber Type	Single Mode 9/125 μ m	
Wavelength	1529...1565 nm	
Common General Specifications		
Size	8 HP (40 mm) Width, 3 RU (133 mm) Height, 100 mm Depth	
Weight	~0.35 kg	
Environmental Conditions	ETS 300019 Part 1-3 Class 3.1E	

DEV 7415 EDFA Optribution Pre-Amplifier Module; 1529...1565 nm; SC/APC

	Value	Condition
Optical Specifications		
Operation Mode	Automatic Output Power Control (APC)	
Input Power Range	-25...-5 dBm	
Max. Gain	25 dB, typ. 27 dB (averaged)	
Adjustable Output Power	0...10 dBm, Step Size 1 dB	
Saturated Output Power	+10 \pm 2dBm, Input Power \geq -15 dBm	
Return Loss	>35 dB	
Noise Figure	<5.5 dB, typ. 4.7 dB	

DEV 7425 EDFA Optribution Boost-Amplifier Module; 1529...1565 nm; SC/APC

	Value	Condition
Optical Specifications		
Operation Mode	Automatic Output Power Control (APC)	
Input Power Range	-3...+10 dBm	
Max. Gain	23 dB	
Adjustable Output Power	0...20 dBm, Step Size 1 dB	
Saturated Output Power	+20 \pm 2 dBm	
Return Loss	>45 dB	
Noise Figure	<5.5 dB, typ. 5 dB	

Order Information

Products

DEV 7415 EDFA Optribution Pre-Amplifier Module; 1529...1565 nm; SC/APC
DEV 7425 EDFA Optribution Boost-Amplifier Module; 1529...1565 nm; SC/APC

Note that the DEV 7113 has to be equipped with Option 34 for the operation of EDFA modules

Optical Connector Options

Option 07 FC/APC Optical Connector
Option 08 E2000/HRL Optical Connector

Contact

DEV Systemtechnik GmbH
Grüner Weg 4A
61169 Friedberg
GERMANY
Phone: +49 6031 6975 100
Fax: +49 6031 6975 114
info@dev-systemtechnik.com
www.dev-systemtechnik.com

Rev. 21-Nov-2019

Disclaimer

The information contained herein is believed to be reliable. DEV Systemtechnik makes no warranties regarding the information contained herein. DEV Systemtechnik assumes no responsibility or liability whatsoever for any of the information and for the use of the information contained herein. The information contained herein is provided "AS IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders.